

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: H01L 23/427, F28D 20/02	A1	(11) International Publication Number: WO 96/28846 (43) International Publication Date: 19 September 1996 (19.09.96)
(21) International Application Number: PCT/GB96/00567 (22) International Filing Date: 12 March 1996 (12.03.96) (30) Priority Data: 9505069.6 14 March 1995 (14.03.95) GB (71) Applicant (for all designated States except US): BARR & STROUD LIMITED [GB/GB]; 1 Linthouse Road, Glasgow G51 4BZ (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): MCQUADE, Thomas [GB/GB]; 14 Hardie Street, Alexandria G83 0RU (GB). (74) Agents: McCALLUM, William, Potter et al.; Cruikshank & Fairweather, 19 Royal Exchange Square, Glasgow G1 3AE (GB).		(81) Designated States: GB, PL, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>

(54) Title: HEAT SINK

(57) Abstract

A heat sink (10) is formed by an aluminium framework composed of thick walls (1) interconnected by thin fins (2). The fins (2) are about 0.10 to 0.20 mm in thickness and are spaced apart by about 0.5 mm to 1.5 mm so as to form cells (4). The cells (4) are filled with a wax.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

HEAT SINK

This invention relates to heat sinks particularly for use with devices, typically electrical or electronic devices for dissipating heat generated by such devices.

Various forms of heat sinks are well known some of which comprise a metal structure having an extended surface area which is exposed to a current of air or liquid as the heat dissipating medium. The air current may be by natural convection or may be fan generated. The liquid may be pumped. Another known form of heat sink, which may also be force cooled, has the metal structure in the form of a framework forming a plurality of cells each housing a body of wax. The wax absorbs heat delivered to one of the metal walls of the framework firstly by temperature increase and then by phase change, from solid to liquid, which is equivalent to a temperature rise of about 150°C.

It is an object of the present invention to provide a new and improved form of heat sink.

According to the present invention there is provided a heat sink comprising a unitary metal framework made of highly thermally-conductive metal, having a pair of metal walls extending substantially parallel to each other and held in spaced mutual relationship by a plurality of metal fins, the fins being substantially parallel to each other and extending transversely to the metal walls, the arrangement being such that the framework defines a plurality of cells between adjacent fins, the cells being substantially filled with a fill material of low thermal conductivity and high latent heat of fusion, characterised by selecting the following features in combination:

- i) the metal is aluminium;
- ii) the fins have a thickness in the range 0.10 to 0.20 mm;
- iii) the spacing between the fins is in the range 0.5 to 1.5 mm;
- iv) the fill material is a wax.

By virtue of the present invention the effective thermal resistance of the heat sink is very low, significantly lower than hitherto which results in the temperature of the metal wall input face being maintained at a comparatively low temperature, typically not more than 5°C greater than the temperature at which the wax fill material melts, until the entirety of the wax fill material has melted. Thus there is highly efficient removal of heat from the heat source and forced cooling of the heat sink is not required. Additionally, the heat sink is comparatively small in size and weight.

It will be understood that the wax fill material may be any one of a number of different waxes having different melt temperatures and latent heat of fusion. Particular waxes may be selected for any particular application of the heat sink, for example from the data listed in the "Handbook of Chemistry and Physics" published from time to time by CRC Press, Inc. (for example, the 65th edition published in 1984/5). The waxes may be long-chain hydrocarbons or silicone based materials. They are selected because they are inexpensive and non-toxic, usually with a melting temperature below 150°C. Also, they have comparatively low thermal conductivity.

An embodiment of the present invention will now be described by way of example with reference to the accompany diagrammatic drawing.

The drawing shows a heat sink 10 comprising a unitary metal framework made of aluminium which is a highly thermally-conductive metal. The framework is formed of a pair of substantially parallel walls 1 which are comparatively thick and which are interconnected and held in spaced mutual relationship by a plurality of spaced fins 2 which are comparatively thin. The fins 2 are substantially parallel to each other and extend transversely, preferably orthogonally, to the walls 1. The spaces between adjacent fins 2 and bonded by the walls 1 define cells 4 which are substantially filled with wax

material of low thermal conductivity and high latent heat of fusion.

The fins 2 are about 0.15 mm thick and have a pitch or spacing 3 which is less than 1.5 mm and for example 0.65mm.

The walls 1 are typically 0.4mm in thickness and are spaced apart typically by about 5 to 10mm although this is not critical. The wax may for example be Naphthalene 1,7-dichloro which has a melting point of about 63°C and a latent heat of fusion of about 250 KJ/kg.

In use, one of the metal walls 1 forms the heat input face of the heat sink 10 and is placed in intimate contact with a device which is to be cooled. Because the aluminium is highly thermally conductive heat is rapidly transferred by conduction to each of the fins 2. The fins 2 are both thin and closely spaced so that there is a very large increase in surface area of fins and wax. The thickness of each wax filled cell 4 is comparatively small so that the thermal path length to the centre of each cell 4 is comparatively small and accordingly the thermal resistance of the sink 10 is comparatively low notwithstanding the low thermal conductivity of the wax. This results in the temperature of the heat input face 1 being held at not more than about 68°C which is only 15°C more than the temperature at which the wax melts until such time as the entirety of the wax has melted. Heat dissipation is therefore highly efficient without any requirement to have forced cooling or large exposed surface areas with fin pitches typically greater than 2mm suitable for natural or forced convection.

Claims

1 A heat sink comprising a unitary metal framework made of highly thermally-conductive metal, having a pair of metal walls (1) extending substantially parallel to each other and held in spaced mutual relationship by a plurality of metal fins (2), the fins (2) being substantially parallel to each other and extending transversely to the metal walls (1), the arrangement being such that the framework defines a plurality of cells (4) between adjacent fins, the cells being substantially filled with a fill material of low thermal conductivity and high latent heat of fusion, characterised by selecting the following features in combination:

- i) the metal is aluminium;
- ii) the fins have a thickness in the range 0.10 to 0.20 mm;
- iii) the spacing between the fins is in the range 0.5 to 1.5 mm;
- iv) the fill material is a wax.

2 A heat sink as claimed in Claim 1, wherein the walls (1) are about 0.4mm in thickness and are spaced apart by a distance in the range 5 to 10mm.

3 A heat sink as claimed in Claim 1 and substantially as hereinbefore described with reference to the accompanying drawing.

1-1




FIG. 1

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 96/00567

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H01L23/427 F28D20/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 H01L F28D F28F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US,A,3 215 194 (J.H. SUNUNU ET AL) 2 November 1965 see the whole document ---	1
X	DE,B,11 06 423 (LICENTIA PATENT-VERWALTUNGS) 10 May 1961 see the whole document ---	1
X	IBM TECHNICAL DISCLOSURE BULLETIN, vol. 27, no. 3, August 1984, page 1779 XP002005397 S.S. FURKAY ET AL: "Clip-On Module Thermal Capacitor" see the whole document ---	1
-/--		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

12 June 1996

Date of mailing of the international search report

19. 06. 96

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+ 31-70) 340-3016

Authorized officer

Zaegel, B

INTERNATIONAL SEARCH REPORT

Inter national Application No

PCT/GB 96/00567

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 017, no. 053 (M-1361), 3 February 1993 & JP,A,04 263000 (AISIN SEIKI CO LTD), 18 September 1992, see abstract ---	1
X	PATENT ABSTRACTS OF JAPAN vol. 016, no. 336 (E-1237), 21 July 1992 & JP,A,04 101450 (MEIDENSHA CORP), 2 April 1992, see abstract -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

Inter: International Application No

PCT/GB 96/00567

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-3215194	02-11-65	NONE	
DE-B-1106423		NONE	